



INSTRUCTIONS

Velour Airbeds

Deluxe Single (KC026-109)

Deluxe Queen (KC026-107)

Serenity Queen (KC026-110)

Your bed includes:

1 x airbed

1 x repair kit

INFLATION

Inflate through the Push n' Pop valve using a hand or electric pump. Use pump as per manufacturer's instructions.

Use the top part of the valve to top-up any air loss during main inflation.

We recommend a Kiwi Camping 12V air pump for fast results.

DEFLATION

Remove the portion of the Push n' Pop valve that releases the air. Fold the bed carefully from the opposite end towards the Push n' Pop valve to complete deflation.

IMPORTANT

1. Do not over inflate as this may cause damage to the bed and void warranty.
2. Do not leave your air bed in direct sunlight as this will weaken the fabric and cause the air pressure to increase.
3. Do not inflate air bed on rough ground, this may cause punctures.
4. Do not place excessive stress on the seams by jumping or bouncing.
5. This is not a floatation device.
6. Maximum weight capacity (evenly distributed):
Deluxe Single: 130kg static weight.
Deluxe Queen: 300kg static weight.
Serenity Queen: 320kg static weight.

TO REPAIR

1. Deflate the bed.
2. Clean and dry the damaged area to remove all traces of oil and grease.
3. Apply the glue, then patch immediately. Apply pressure for 2 minutes.
4. Apply glue to the edge of the patch for sealing purposes.
5. Allow at least 30 minutes drying time before re-inflating the bed.